

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (currently amended) An optical information recording device, wherein a mark or a space having a length corresponding to a length of a data recording code is formed by irradiating a rotating optical information recording medium with laser light to change optical characteristics of a photosensitive recording layer, and

the mark is formed by ~~irradiation of~~ irradiating the rotating optical information recording medium with the laser light with a power being switched among a plurality of power levels including at least a recording power level and an erase power level,

the device comprising:

a linear velocity setting ~~circuit~~ portion for setting a first linear velocity v1 and a second linear velocity v2 that is higher than the first linear velocity v1 for the rotating optical information recording medium;

a recording pulse generation ~~circuit~~ portion for generating a recording pulse signal composed of a recording pulse and/or a recording pulse train, depending on a result of setting by the linear velocity setting ~~circuit~~ portion; and

a laser drive ~~circuit~~ portion for irradiating the optical information recording medium with the laser light based on the recording pulse signal generated by the recording pulse generation ~~circuit~~ portion,

wherein the laser drive ~~circuit~~ portion controls a power level of the laser light in such a manner that

$P_{bt1} \leq P_{e1}$ and $P_{e2} < P_{bt2} \leq P_{wa2} < P_{wa2}$ is satisfied,

where P_{bt1} represents a first inter-pulse power level indicating a power level between recording pulses in the recording pulse train for the first linear velocity v1,

P_{bt2} represents a second inter-pulse power level indicating a power level between the recording pulses in the recording pulse train for the second linear velocity v2,

Pwa2 represents a recording power level indicating a power level of the recording power for the second linear velocity v2,

Pe1 represents a first erase power level indicating a power level of the erase power for the first linear velocity v1, and

Pe2 represents a second erase power level indicating a power level of the erase power for the second linear velocity v2.

2. (cancel)

3. (currently amended) The optical information recording device according to claim 1, wherein the laser drive ~~circuit~~ portion controls the inter-pulse power level Pbt so that (Pbt-Pe) is increased between Pbt1 and Pbt2, depending on an increase in the linear velocity v,

where Pbt represents a power level between the recording pulses in the recording pulse train for a linear velocity v of $v_1 < v < v_2$, and

Pe represents a power level of the erase power for the linear velocity v.

4. (currently amended) The optical information recording device according to claim 1, wherein a waveform of the recording pulse is a rectangular wave for a ~~predetermined~~ linear velocity of v0 ~~or more, v0~~ having a relationship $v_1 < v_0 < v_2$.

5. (currently amended) An optical information recording device, wherein a mark or a space having a length corresponding to a length of a data recording code is formed by irradiating a rotating optical information recording medium with laser light to change optical characteristics of a photosensitive recording layer, and

the mark is formed by ~~irradiation of~~ irradiating the rotating optical information recording medium with the laser light with a power being switched among a plurality of power levels including at least a recording power level and an erase power level,

the device comprising:

a linear velocity setting ~~circuit~~ portion for setting a first linear velocity v1 and a second linear velocity v2 that is higher than the first linear velocity v1 for the rotating optical information recording medium;

a recording pulse generation ~~circuit~~ portion for generating a recording pulse signal composed of a recording pulse and/or a recording pulse train, depending on a result of setting by the linear velocity setting ~~circuit~~ portion; and

a laser drive ~~circuit~~ portion for irradiating the optical information recording medium with the laser light based on the recording pulse signal generated by the recording pulse generation ~~circuit~~ portion,

wherein the laser drive ~~circuit~~ portion controls a power level of the laser light in such a manner that

$P_{bt1} \leq P_{e1}$ and $P_{e2} < P_{wb2} < P_{wa2}$ is satisfied, and

a waveform of the laser light for the second linear velocity v2 is set to be a stepwise waveform such that a recording pulse of the power level Pwb2 is provided immediately after a recording pulse of the power level Pwa2,

where Pbt1 represents a first inter-pulse power level indicating a power level between recording pulses in the recording pulse train for the first linear velocity v1,

Pwa2 represents a recording power indicating a power level of the recording power for the second linear velocity v2,

Pwb2 represents a second recording power indicating a power level of a second recording power for the second linear velocity v2,

Pe1 represents a first erase power level indicating a power level of the erase power for the first linear velocity v1, and

Pe2 represents a second erase power level indicating a power level of the erase power for the second linear velocity v2.

6. (currently amended) The optical information recording device according to claim 5, wherein the recording pulse generation ~~circuit~~ portion sets a width of each step of the stepwise waveform to be longer than 1/2 of a channel clock cycle for the second linear velocity v2.

7. (currently amended) An optical information recording device, wherein a mark or a space having a length corresponding to a length of a data recording code is formed by irradiating a rotating optical information recording medium with laser light to change optical characteristics of a photosensitive recording layer, and

the mark is formed by ~~irradiation of~~ irradiating the rotating optical information recording medium with the laser light with a power being switched among a plurality of power levels including at least a recording power level and an erase power level,

the device comprising:

a linear velocity setting ~~circuit~~ portion for setting a first linear velocity v_1 , which is a lower limit, and a second linear velocity v_2 , which is an upper limit, with respect to the rotating optical information recording medium,

a recording pulse generation ~~circuit~~ portion for generating a recording pulse signal composed of a recording pulse and/or a recording pulse train, depending on a result of setting by the linear velocity setting ~~circuit~~ portion; and

a laser drive ~~circuit~~ portion for irradiating the optical information recording medium with the laser light based on the recording pulse signal generated by the recording pulse generation ~~circuit~~ portion,

wherein $P_{bt1} \leq P_{e1}$ and $P_{e2} < P_{wb2} < P_{wa2}$ are satisfied,

the laser light is irradiated while switching powers among the recording power level, the first erase power level and the first inter-pulse power level, when the linear velocity v is $v_1 < v < v_0$,

a waveform of the laser light is set to be a stepwise waveform such that a recording pulse of the power level P_{wb2} is provided immediately after a recording pulse of the power level P_{wa2} , when the linear velocity v is $v_0 < v < v_2$, and

the power level P_{wb} of the second recording power is controlled so that $(P_{wb} - P_e)$ is increased, depending on an increase in the linear velocity v ,

where P_{bt1} represents a first inter-pulse power level indicating a power level between recording pulses in the recording pulse train for the first linear velocity v_1 ,

P_{wa2} represents a recording power indicating a power level of the recording power for the second linear velocity v_2 ,

Pwb2 represents a second recording power indicating a power level of a second recording power for the second linear velocity v2,

Pe1 represents a first erase power level indicating a power level of the erase power for the first linear velocity v1,

Pe2 represents a second erase power level indicating a power level of the erase power for the second linear velocity v2,

$v1 < v0 < v2$ is satisfied,

Pwb represents a power level of the second recording power for a linear velocity v of $v1 < v < v2$, and

Pe represents a power level of the erase power for the linear velocity v.

8. (currently amended) The optical information recording device according to claim 7, wherein the recording pulse generation ~~circuit~~ portion sets a width of each step of the stepwise waveform to be longer than 1/2 of a channel clock cycle for the second linear velocity v2.

9. (currently amended) An optical information recording device, wherein a mark or a space having a length corresponding to a length of a data recording code is formed by irradiating a rotating optical information recording medium with laser light to change optical characteristics of a photosensitive recording layer, and

the mark is formed by ~~irradiation of~~ irradiating the rotating optical information recording medium with the laser light with a power being switched among a plurality of power levels including at least a recording power level and an erase power level,

the device comprising:

a linear velocity setting ~~circuit~~ portion for setting a first linear velocity v1, which is a lower limit, and a second linear velocity v2, which is an upper limit, with respect to the rotating optical information recording medium,

a recording pulse generation ~~circuit~~ portion for generating a recording pulse signal composed of a recording pulse and/or a recording pulse train, depending on a result of setting by the linear velocity setting ~~circuit~~ portion; and

a laser drive ~~circuit~~ portion for irradiating the optical information recording medium with the laser light based on the recording pulse signal generated by the recording pulse generation ~~circuit~~ portion,

wherein duty ratios of the recording pulses are set to be constant when the linear velocity v is $v_1 \leq v < v_0$ and when the linear velocity v is $v_0 < v \leq v_2$, respectively, and the power level P_{bt} of the inter-pulse is controlled so that $(P_{bt}-P_e)$ is increased, depending on an increase in the linear velocity v , when the linear velocity v is $v_1 \leq v < v_0$ and when the linear velocity v is $v_0 < v \leq v_2$, respectively,

where P_{bt} represents a power level between the recording pulses in the recording pulse train for a linear velocity v of $v_1 < v < v_2$, P_e represents a power level of the erase power for the linear velocity v , and $v_1 < v_0 < v_2$.

10. (original) The optical information recording device according to claim 9, wherein a correction amount of an edge position of the recording pulse is controlled to be constant with reference to a channel clock cycle when the linear velocity v is $v_1 \leq v < v_0$ and when the linear velocity v is $v_0 < v \leq v_2$, respectively.

11. (currently amended) An optical information recording method, wherein a mark or a space having a length corresponding to a length of a data recording code is formed by irradiating a rotating optical information recording medium with laser light to change optical characteristics of a photosensitive recording layer, and

the mark is formed by ~~irradiation of~~ irradiating the rotating optical information recording medium with the laser light with a power being switched among a plurality of power levels including at least a recording power level and an erase power level,

the method comprising:

a linear velocity setting step of setting a first linear velocity v_1 and a second linear velocity v_2 that is higher than the first linear velocity v_1 for the rotating optical information recording medium;

a recording pulse generation step of generating a recording pulse signal composed of a recording pulse and/or a recording pulse train, depending on a result of setting by the linear velocity setting step; and

a laser drive step of irradiating the optical information recording medium with the laser light based on the recording pulse signal generated by the recording pulse generation step,

wherein in a laser drive step, a power level of the laser light is controlled in such a manner that

$P_{bt1} \leq P_{e1}$ and $P_{e2} < P_{bt2} \leq P_{wa2} < P_{wa2}$ is satisfied,

where P_{bt1} represents a first inter-pulse power level indicating a power level between recording pulses in the recording pulse train for the first linear velocity v_1 ,

P_{bt2} represents a second inter-pulse power level indicating a power level between the recording pulses in the recording pulse train for the second linear velocity v_2 ,

P_{wa2} represents a recording power level indicating a power level of the recording power for the second linear velocity v_2 ,

P_{e1} represents a first erase power level indicating a power level of the erase power for the first linear velocity v_1 , and

P_{e2} represents a second erase power level indicating a power level of the erase power for the second linear velocity v_2 .

12. (cancel)

13. (currently amended) The optical information recording method according to claim 11, wherein in the laser drive step, the inter-pulse power level P_{bt} is controlled so that $(P_{bt}-P_e)$ is increased between P_{bt1} and P_{bt2} , depending on an increase in the linear velocity v ,

where P_{bt} represents a power level between the recording pulses in the recording pulse train for a linear velocity v of $v_1 < v < v_2$, and

P_e represents a power level of the erase power for the linear velocity v .

14. (currently amended) The optical information recording method according to claim 11, wherein a waveform of the recording pulse is a rectangular wave for a ~~predetermined~~ linear velocity of v_0 ~~or more, v_0~~ having a relationship $v_1 < v_0 < v_2$ ~~v_0~~ .

15. (currently amended) An optical information recording method, wherein a mark or a space having a length corresponding to a length of a data recording code is formed by irradiating a rotating optical information recording medium with laser light to change optical characteristics of a photosensitive recording layer, and

the mark is formed by ~~irradiation of~~ irradiating the rotating optical information recording medium with the laser light with a power being switched among a plurality of power levels including at least a recording power level and an erase power level,

the method comprising:

a linear velocity setting step of setting a first linear velocity $v1$ and a second linear velocity $v2$ that is higher than the first linear velocity $v1$ for the rotating optical information recording medium;

a recording pulse generation step of generating a recording pulse signal composed of a recording pulse and/or a recording pulse train, depending on a result of setting by the linear velocity setting step; and

a laser drive step of irradiating the optical information recording medium with the laser light based on the recording pulse signal generated by the recording pulse generation step,

wherein in the laser drive step, a power level of the laser light is controlled in such a manner that

$P_{bt1} \leq P_{e1}$ and $P_{e2} < P_{wb2} < P_{wa2}$ is satisfied, and

a waveform of the laser light for the second linear velocity $v2$ is caused to be a stepwise waveform such that a recording pulse of the power level P_{wb2} is provided immediately after a recording pulse of the power level P_{wa2} ,

where P_{bt1} represents a first inter-pulse power level indicating a power level between recording pulses in the recording pulse train for the first linear velocity $v1$,

P_{wa2} represents a recording power indicating a power level of the recording power for the second linear velocity $v2$,

P_{wb2} represents a second recording power indicating a power level of a second recording power for the second linear velocity $v2$,

P_{e1} represents a first erase power level indicating a power level of the erase power for the first linear velocity $v1$, and

Pe2 represents a second erase power level indicating a power level of the erase power for the second linear velocity v2.

16. (original) The optical information recording method according to claim 15, wherein in the recording pulse generation step, a width of each step of the stepwise waveform is set to be longer than 1/2 of a channel clock cycle for the second linear velocity v2.

17. (currently amended) An optical information recording method, wherein a mark or a space having a length corresponding to a length of a data recording code is formed by irradiating a rotating optical information recording medium with laser light to change optical characteristics of a photosensitive recording layer, and

the mark is formed by ~~irradiation of~~ irradiating the rotating optical information recording medium with the laser light with a power being switched among a plurality of power levels including at least a recording power level and an erase power level,

the method comprising:

a linear velocity setting step of setting a first linear velocity v1, which is a lower limit, and a second linear velocity v2, which is an upper limit, with respect to the rotating optical information recording medium,

a recording pulse generation step of generating a recording pulse signal composed of a recording pulse and/or a recording pulse train, depending on a result of setting by the linear velocity setting ~~circuit~~ portion; and

a laser drive step of irradiating the optical information recording medium with the laser light based on the recording pulse signal generated by the recording pulse generation ~~circuit~~ portion,

wherein $P_{bt1} \leq P_{e1}$ and $P_{e2} < P_{wb2} < P_{wa2}$ are satisfied,

the laser light is emitted while switching powers among the recording power level, the first erase power level and the first inter-pulse power level, when the linear velocity v is $v1 < v < v0$,

a waveform of the laser light is caused to be a stepwise waveform such that a recording pulse of the power level P_{wb2} is provided immediately after a recording pulse of the power level P_{wa2} , when the linear velocity v is $v_0 < v < v_2$, and

the power level P_{wb} of the second recording power is controlled so that $(P_{wb} - P_e)$ is increased, depending on an increase in the linear velocity v ,

where P_{bt1} represents a first inter-pulse power level indicating a power level between recording pulses in the recording pulse train for the first linear velocity v_1 ,

P_{wa2} represents a recording power indicating a power level of the recording power for the second linear velocity v_2 ,

P_{wb2} represents a second recording power indicating a power level of a second recording power for the second linear velocity v_2 ,

P_{e1} represents a first erase power level indicating a power level of the erase power for the first linear velocity v_1 ,

P_{e2} represents a second erase power level indicating a power level of the erase power for the second linear velocity v_2 ,

$v_1 < v_0 < v_2$,

P_{wb} represents a power level of the second recording power for a linear velocity v of $v_1 < v < v_2$, and

P_e represents a power level of the erase power for the linear velocity v .

18. (original) The optical information recording method according to claim 17, wherein in the recording pulse generation step, a width of each step of the stepwise waveform is set to be longer than $1/2$ of a channel clock cycle for the second linear velocity v_2 .

19. (currently amended) An optical information recording method, wherein a mark or a space having a length corresponding to a length of a data recording code is formed by irradiating a rotating optical information recording medium with laser light to change optical characteristics of a photosensitive recording layer, and

the mark is formed by ~~irradiation of~~ irradiating the rotating optical information recording medium with the laser light with a power being switched among a plurality of power levels including at least a recording power level and an erase power level,

the method comprising:

a linear velocity setting step of setting a first linear velocity v_1 , which is a lower limit, and a second linear velocity v_2 , which is an upper limit, with respect to the rotating optical information recording medium,

a recording pulse generation step of generating a recording pulse signal composed of a recording pulse and/or a recording pulse train, depending on a result of setting by the linear velocity setting ~~circuit~~ portion; and

a laser drive step of irradiating the optical information recording medium with the laser light based on the recording pulse signal generated by the recording pulse generation ~~circuit~~ portion,

wherein duty ratios of the recording pulses are set to be constant when the linear velocity v is $v_1 \leq v < v_0$ and when the linear velocity v is $v_0 < v \leq v_2$, respectively, and

the power level P_{bt} of the inter-pulse is controlled so that $(P_{bt} - P_e)$ is increased, depending on an increase in the linear velocity v , when the linear velocity v is $v_1 \leq v < v_0$ and when the linear velocity v is $v_0 < v \leq v_2$, respectively,

where P_{bt} represents a power level between the recording pulses in the recording pulse train for a linear velocity v of $v_1 < v < v_2$, P_e represents a power level of the erase power for the linear velocity v , and $v_1 < v_0 < v_2$.

20. (original) The optical information recording method according to claim 19, wherein a correction amount of an edge position of the recording pulse is controlled to be constant with reference to a channel clock cycle when the linear velocity v is $v_1 \leq v < v_0$ and when the linear velocity v is $v_0 < v \leq v_2$, respectively.

21. (currently amended) The optical information recording method according to ~~any one of claims 11, 15, 17 and 19~~ claim 11, wherein data is recorded onto the optical information recording medium using a CAV recording technique.

22. (original) An optical information recording medium to be used for recording data by the optical information recording method according to claim 11, comprising information recorded thereon that indicates values of the first inter-pulse power level Pbt1 and the second inter-pulse power level Pbt2.

23. (original) An optical information recording medium to be used for recording data by the optical information recording method according to claim 15, comprising information recorded thereon that indicates values of the first inter-pulse power level Pbt1 and the second recording power level Pwb2.

24. (original) An optical information recording medium to be used for recording data by the optical information recording method according to claim 17, comprising information recorded thereon that indicates a value of the second recording power level Pwb2.

25. (original) An optical information recording medium to be used for recording data by the optical information recording method according to claim 17, comprising information recorded thereon that indicates a value of the first inter-pulse power level Pbt1.

26. (original) An optical information recording medium to be used for recording data by the optical information recording method according to claim 19, comprising information recorded thereon that indicates values of the inter-pulse power level Pbt and the duty ratio of the recording pulse.

27. (original) An optical information recording medium to be used for recording data by the optical information recording method according to claim 20, comprising information recorded thereon that indicates a value of a correction amount of an edge position of the recording pulse.

28. (New) The optical information recording method according to claim 15, wherein data is recorded onto the optical information recording medium using a CAV recording technique.

29. (New) The optical information recording method according to claim 17, wherein data is recorded onto the optical information recording medium using a CAV recording technique.

30. (New) The optical information recording method according to claim 19, wherein data is recorded onto the optical information recording medium using a CAV recording technique.